



Messmate

Messmate is a highly versatile product suitable for a variety of commercial and residential applications.

Common Name	Messmate
Look & features	Medium and even texture with frequent gum veins
Botanical name	Eucalyptus obliqua
Colour	Pale through to light brown
Common uses	A wide range of internal applications, including cladding, flooring, and bespoke joinery

Ranging in colour from pale to light brown, this timber offers both character and resilience while being an impressive addition to any project.

Ideal for commercial applications where a light and airy ambience is required, Messmate is widely used within the residential building industry across various applications, including cladding, flooring, and bespoke joinery items.

Recognised for its unique grain and rich patina, Messmate adorns many notable projects. With an incredible colour palette and ability to charm any space, Messmate is available to order now.

Properties

Density (kg/m³)	
GD	1,080
ADD	750
Hardness kN (Janka)	
Green	5.3
Dry	7.1
Durability class	3
Strength group	S3/SD3
Joint group	J3/JD3
Shrinkage	
Radial % (approx.)	> 5.0
Tangential % (approx.)	11.3
Structural grades	
Unseasoned	F11/F14/F17
Seasoned	F22/F27+
Toughness (Nm)	
Green	Medium
Dry	Medium
Early fire hazard indices	
Ignitability	13
Spread of flame	5
Smoke development	3
Termite resistant	No
Lyctid-susceptible sapwood	Yes

